Section 11 68 43 – Exterior Scoreboards

8450 LED Football Scoreboard

Part 1 -	General
----------	---------

1.01 Summary

1.01.1 Section includes a single-sided, outdoor, electronic, multisport scoreboard

1.02 References

- 1.02.1 UL 48 Standard for Safety for Electric Signs, 15th Edition
- 1.02.2 National Electrical Code
- 1.02.3 Federal Communication Commission (FCC) Rules, Part 15

1.03 Submittals

- 1.03.1 Product Data: Manufacturer's illustrations, diagrams, pictures, and documentation for scoreboard(s) and accessories
- 1.03.2 Documentation: Wiring diagram, installation manual, and operation manuals

1.04 Delivery, Storage, and Handling

- 1.04.1 Product to be delivered to customer specified location
- 1.04.2 Product to be stored in a clean, dry, environment prior to installation

1.05 Site Conditions

1.05.1 Ambient Conditions

- A. Concrete footings must be complete and had ample time to cure
- B. Mounting structure must be complete and fully secured
- C. Verify mounting structure can handle the scoreboard's weight with accessories and any options
- D. Verify mounting structure can handle the scoreboard's wind load
- E. Confirm installation can be performed within safe and acceptable weather conditions

1.06 Warranty

1.06.1 Manufacturer Warranty

- A. Scoreboard is covered under a five (5) year general manufacturer defect part warranty
- B. Radios (optional) are covered under a two (2) year manufacturer defect part warranty
- C. Console AC adapter and internal battery pack are covered under a one (1) year manufacturer defect part warranty
- D. Provide Technical Phone support Monday through Friday 8:00am to 5:00pm Central Standard Time. Limited phone support available until 9:00pm on weekdays, and from 8:00am to 12:00pm on Saturdays

Part 2 - Products

2.01 Manufacturers

2.01.1 All American Scoreboards. 401 S. Main Street, Pardeeville, WI 53954

2.01.2

2.01.3

2.02 Equipment: 8450 Electronic Scoreboard

2.02.1 Description: All American Scoreboards 8450, single sided Football scoreboard. Multi-sport functionality for Football, Soccer, Field Hockey, Baseball and a Segment Timer.

2.02.2 Scoreboard Design Criteria

- A. Cabinet Construction
 - 1. 4" extruded aluminum case, .093" thick
 - 2. Shatterproof polycarbonate face panel
 - 3. Nine (9) standard colors, with custom color matching available
 - 4. 5' high x 8' wide x 5" deep (1.52m x 2.44m x .13m)
 - 5. Net Weight of 200lbs (90.72kg)

B. LED Panels

- Scoreboard displays Game Time, Home Score, Guest Score, and Period
- 2. All digits are bright red, 7-segment
- 3. Clock Digits: 18" high, displaying 0:00-99:59, with user configurable last minute tenths
- 4. Score Digits: 18" high, displaying 0-99
- 5. Period Digit: 14" high, displaying 0-9

C. Captions

- 1. All captions are white vinyl
- 2. Home and Guest Captions: 6" high
- 3. Period Caption: 3.5" high
- 4. Clock Colon Dots: 2.5" in diameter

D. Standard Equipment

- 1. Built-in shatterproof face panel covering all LEDs, requiring no additional protective screens or netting
- 2. Twisted pair hardwire control
- 3. Time of Day Clock when not connected to a console

E. Optional Equipment

- 1. 2.4GHz Wireless Radio Control (Hardwire backup is available)
- 2. Ad-panels
- 3. Green, White, or Amber colored LEDs available
- 4. 120dB external trumpet style horn

2.02.3 Console Design Criteria

- A. 8000 Series Multi-Sport Console
- B. Console Construction: Extruded aluminum with raised molded sides
- C. Console Dimensions: 13.25" (33.66cm) wide x 5" (12.7cm) high x 9" (22.86cm) deep
- D. Net weight: 6lbs (2.72kg)
- E. Microprocessor control with membrane keyboard
- F. Standard Console Features:
 - 1. Internal battery pack
 - 2. Capability to control any single or multiple scoreboard(s), timer(s), Electronic Message Center(s) and/or stat panels
 - 3. Easy to read large 2x20 character LCD screen
 - 4. Multi-sport functionality with slip sheets for membrane keypad layout
 - 5. AC power adapter, 12V, 2.0A for AC power operation and internal battery charging
 - 6. Basic setup instructions on the underside of the console

- 7. Advanced console configuration options are available via a USB connected PC
- 8. USB updatable firmware, when attached to an internet connected PC
- 9. Full sport configuration setup through the console, including period time, number of periods, two (2) delay of game timers, time out length, time outs allowed, automatic horn, last minute tenths.
- 10. Visual indicators for radio operation, running clock, battery, and horn
- 11. Hand-held timer pendant switch for clock stop/start
- 12. Dimming control for 8 levels of Scoreboard LED brightness
- G. Optional Console Features
 - 1. Hand-held remote functionality with console add-on
 - 2. Hard-Cover carrying case
 - 3. 2.4 GHz radio for wireless control

Part 3 - Execution

3.01 Examination

3.01.1 Verify that the mounting structure is ready to receive the scoreboard. The I-Beams must be level and plumb, and the concrete had ample time to cure.

3.02 Installation – Scoreboard

- 3.02.1 All power wires and any control wires will be routed in conduit. Power to the scoreboard(s)/display(s) as well as any cable race-ways shall be installed as shown on the electrical plans by the Electrical contractor or architect's specifications
- 3.02.2 Mount and install the scoreboard(s) and ad-panel displays to the I-Beams in the manner described in the supplied manufacture's instructions. Verify that the scoreboard is mounted plumb, level, and all fasteners are secure.

3.03 Installation – Hardwire Control

- 3.03.1 Install any ports, jacks, and/or electrical boxes in the specified locations per the project plans.
- 3.03.2 Confirm all control wiring is performed in accordance with manufacturer's specifications.
- 3.03.3 Test the operation of the scoreboard and control console. Confirm the console is able to control all scoreboard functions, digits, and indicators.
- 3.03.4 Leave the console, and any accessories with the scoreboard owner, or owner's designated representative.

End of Section 11 68 43