

## ARCHITECTS SPECIFICATIONS MODEL 8201SP LED BASKETBALL SCOREBOARD

## INDOOR SCOREBOARD PLYR FLS PNTS PLYR FLS PNTS 8201SP **Basketball** For Volleyball/Basketball Statpanels, use 8601SP ALL AMERICAN ALL AMERICAN **OVERALL DIMENSION** 6'10"high x 4' wide x 5" deep. INFORMATION DISPLAYED Player Number, Foul, Points. **DIGITS** Bright Red and Amber, 7-Segment LEDs. **PLAYER NUMBER** 8" High Amber Digits, Shall register 00 - 99. **FOULS** 8" High Red Digits, Shall register 0 - 9. **POINTS** 8" High Amber Digits, Shall register 0 - 99. **CAPTIONS** White vinyl letters. CONSTRUCTION 5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green, custom colors available). **ELECTRONICS** 100% solid state, microprocessor controlled system. **HORN** Horn not included. Horn is included with main scoreboard (recommend 8218). **SERVICING** Front access for ease of servicing. Plug in modules for ease of replacement. MICROPROCESSOR CONTROL Extruded Aluminum, high impact low profile microprocessor control console, latest state **CONSOLE** of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with ALL AMERICAN membrane keyboard provides for direct entry of all information. A single console may control game and stat information, or another console can be connected to share scoring duties. Computer interface also available. Radio Control is available. STATISTITION INTERFACE May also be controlled via All American Statistition Interface (AASI). A Windows® PC with USB connection and Stat Crew \* software are required for AASI. JUNCTION BOX One junction box 5" x 3" with cover and plug. (Hardwire) Can connect directly to main 8000 series scoreboard. **DATA CABLE** Twisted pair, direct burial, RJ45 Connectors. Hardwired connection is recommended because stat panels can connect directly to main 8000 series scoreboard. 120VAC. Minimum one 20A circuit is recommended. **POWER REQUIREMENTS INSTALLATION** May be mounted to nearly any wall surface. WEIGHT Net 85 lbs / Shipping 180 lbs. WARRANTY

Windows ® is a registered trademark of the Microsoft Corporation. Stat Crew® software is a trademark of Stat Crew Software, Inc.



for parts in warranty. Union label.

Five year guarantee against defects in materials and workmanship. Factory repair service