

## ARCHITECTS SPECIFICATIONS MODEL 8218EMC LED BASKETBALL SCOREBOARD

## INDOOR SCOREBOARD GO TEAM GO!! 8218EMC **HOME BASKETBALL** Wrestling T.O.L. Volleyball **Segment Timer** BONUS BONUS • PERIOD + Electronic Message Canter PLAYER FOUL FOULS FOULS SCORE MATCH **SCORE OVERALL DIMENSION** 8'2"high x 12' wide x 5" deep. INFORMATION DISPLAYED Game Time, Home and Guest Score, Period, Time Outs Left, Fouls, Double Bonus, Possession. May also be used for wrestling and volleyball. **DIGITS** Bright Red and Amber, 7-Segment LEDs. **GAMETIME** 18" High Red Digits, Shall register 0:00 - 99:59, 1/10 second capable. May display Time Of Day when not in use and during select sports. 16" High Amber Digits, Shall register 0-199. **SCORE** 14" High Red Digits, Shall register 1-4. **PERIOD** T.O.L. 14" High Amber Digits, Shall Register 1-9. **FOULS** 14" High Red Digits, Shall Register 1-19. **PLAYER** 14" High Amber Digits, Shall Register 00-99. 14" High Amber Digits, Shall register 0-9. **PLAYER FOUL POSSESSION** Indicated by 2" Red LED Indicators. **BONUS / DOUBLE BONUS** Indicated by 2" Amber LED Indicators. White vinyl letters. **CAPTIONS EMC** Built in Everbrite Message Center: a text only message center with 8" character height. Send 99 different looped programs and 99 different messages instantly during gameplay. Second console required for instant messages. CONSTRUCTION 5" extruded aluminum frame, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Navy, Blue, Bright Blue, Violet, Maroon, Red, Forest Green, Green, custom colors available). **ELECTRONICS** 100% solid state, microprocessor controlled system. **HORN** Includes external 100 dB horn. 120dB Trumpet horn is available. SERVICING Front access for ease of servicing. Plug in modules for ease of replacement. MICROPROCESSOR CONTROL Extruded Aluminum, high impact low profile microprocessor control console, latest state **CONSOLE** of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weight: 6 lbs. Microprocessor til trein i to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control available. JUNCTION BOX One junction box 5" x 3" with cover and plug. (Hardwire) **DATA CABLE** Twisted pair, direct burial, RJ45 Connectors. **POWER REQUIREMENTS** 120VAC. Minimum one 20A circuit is recommended. **INSTALLATION** May be mounted to nearly any wall surface. **WEIGHT** Net 301 lbs / Shipping 420 lbs. **WARRANTY** Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.

