

ARCHITECTS SPECIFICATIONS MODEL 8333LS LED LINE SCORE BASEBALL SCOREBOARD

SCOREBOARDS	
OUTDOOR SCOREBOARD	
8333LS	BALL STRIKE OUT OUT AT BAT
Line Score Baseball	1 2 3 4 5 6 7 8 9 R OH OE
	HOME
OVERALL DIMENSION	8' high x 26' wide x 4.75" deep.
INFORMATION DISPLAYED	Home Line Score, Guest Line Score, Ball, Strike, Out, Runs, Hits, Errors, At Bat,
IN CHIMATION DISI EALED	Hit, Error Indicators, On Base
DIGITS	Bright Red, 7-Segment LEDs.
SCORING	14" High Digits, Inning shall register 0-9. Runs shall register 0-99.
HITS	14" High Digits, Shall register 0-99.
ERRORS	14" High Digits, Shall register 0-9.
BALL	21" High Digits, Shall Register 1-3.
STRIKE	21" High Digits, Shall Register 1-2.
OUT	21" High Digits, Shall Register 1-2.
AT BAT	21" High Digits, Shall register 0-99.
HIT or ERROR	4" Bulls Eye, Displays on or off.
RUNNERS ON BASE	4" Bulls Eye, Displays runners on first, second and/or third base.
CAPTIONS	White vinyl letters.
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal,
	finished in choice of colors (Black, Dark Blue, Bright Blue, Violet, Maroon,
	Red, Dark Green, Green, custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR	Extruded Aluminum, high impact low profile microprocessor control
CONTROL CONSOLE	console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9"
	deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard
	provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Twisted pair, direct burial.
POWER REQUIREMENTS	115 VAC, 60 Hz. Minimum one 20A circuit is recommended.
INSTALLATION	May be installed on three posts. Mounting brackets are supplied with
	scoreboard.
WEIGHT	Net 850 lbs. / Shipping 1100 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory
	repair service for parts in warranty. Union label.