

ARCHITECTS SPECIFICATIONS MODEL 8335LSTN LED LINE SCORE BASEBALL SCOREBOARD

SCOREBOARDS	
SCOREBOARD	DALL OF STRUCK OF STRUCK
8335LSTN	BALL STRIKE OUT OUT BAT BAT
Line Score Baseball	1 2 3 4 5 7 6 8 9 10 R OH OE
	MUSTANGS [] [] [] [] [] [] [] [] [] [] [] [] []
	EAGLES 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
OVERALL DIMENSION	8' high x 28' wide x 4" deep.
INFORMATION DISPLAYED	Home Line Score, Guest Line Score, Ball, Strike, Out, Runs, Hits, Errors, At
	Bat, Hit, Error Indicators
DIGITS	10 Inning Line Score, Runs, Hits, Errors: 14" high Digits, Bright Red LED's.
	Ball, Strike, Out, At Bat: 21" high characters, Super Bright Red LED's.
	On Base, Hit & Error Indicators: 4" Bull's Eyes
SCORING	Inning shall register 0-9. Runs shall register 0-99.
HITS	Shall register 0-99.
ERRORS	Shall register 0-9.
BALL	Shall Register 1-4.
STRIKE	Shall Register 1-3.
OUT	Shall Register 1-3.
AT BAT	shall register 0-99.
HIT or ERROR	Displays Hit or Error Indication.
RUNNERS ON BASE	Displays runners on first, second and/or third base.
CAPTIONS	12" high white letters indicate Ball, Strike and Out, At Bat, Guest, Home.
	9" high white letters indicate Innings 1-9 and Runs.
ELECTRONIC CAPTIONS	8x40 Matrix. Displays average of 8-10 Super Bright 8.25" LED Characters.
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal,
	finished in choice of colors (Black, Navy, Blue, Bright Blue, Purple, Maroon,
ELECTRONICS	Red, Forest Green, Green, custom colors available). 100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR	Extruded Aluminum, high impact low profile microprocessor control
CONTROL CONSOLE	console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9"
CONTROL CONSOLL	deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable
	(hardwire). Microprocessor control console with membrane keyboard
	provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Two (2) twisted pair, shielded direct burial.
POWER REQUIREMENTS	115 VAC, 60 Hz, 10A. Minimum one 15A circuit is recommended.
INSTALLATION	May be installed on three posts. Mounting brackets are supplied with
	scoreboard.
WEIGHT	Net 1200 lbs. / Shipping 1440 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory
	repair service for parts in warranty. Union label.