ALL AMERICAN

ARCHITECTS SPECIFICATIONS MODEL 8338LS LED LINE SCORE BASEBALL SCOREBOARD

SCOREBOARDS	MODEL 8338LS LED LINE SCORE BASEBALL SCOREBOARD
OUTDOOR SCOREBOARD 8338LS	AT BALL STRIKE OUT H/E
Line Score Baseball	
Ellic Score Busebull	1 2 3 4 5 6 7 8 9 10 R H E
	HOME 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
OVERALL DIMENSION	8' high x 28' wide x 4.75" deep.
INFORMATION DISPLAYED	Home Line Score, Guest Line Score, Ball, Strike, Out, Runs, Hits, Errors, At Bat, Hit, Error
DIGITS	Bright Red, 7-Segment LEDs.
SCORING	14" High Digits, Inning shall register 0-9. Runs shall register 0-99.
HITS	14" High Digits, Shall register 0-99.
ERRORS	14" High Digits, Shall register 0-9.
BALL	21" High Digits, Shall Register 1-3.
STRIKE	21" High Digits, Shall Register 1-2.
OUT	21" High Digits, Shall Register 1-2.
AT BAT	21" High Digits, Shall register 0-99.
HIT or ERROR	21" High Digits, Shall register 00-99, H, E, E1-E9
CAPTIONS	White vinyl letters (Electonic Team Names Available).
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal, finished in
	choice of colors (Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green,
	custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL	Extruded Aluminum, high impact low profile microprocessor control console, latest
CONSOLE	state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs.
112 112 118	Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio
	Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Twisted pair, direct burial, RJ45.
POWER REQUIREMENTS	115 VAC, 60 Hz. Minimum one 20A circuit is recommended.
INSTALLATION	May be installed on three posts. Mounting brackets are supplied with scoreboard.
WEIGHT	Net 918 lbs. / Shipping 1170 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service
	for parts in warranty. Union label.