

8389PC Baseball	BALL STRIKE OUT HIT ERROR PITCH COUNT
OVERALL DIMENSION	8' high x 8' wide x 4.75" deep.
INFORMATION DISPLAYED	Home Score, Guest Score, Inning, Ball, Strike, Out, Hit/Error
DIGITS	7-Segment, Bright Red LEDs.
SCORING	18" High Digits, Shall register 0-99.
INNING	16" High Digits, Shall register 1-19.
PITCH COUNT	14" High Digits, Shall register 0-199.
BALL	3" Bulls Eye Indicators.
STRIKE	3" Bulls Eye Indicators.
OUT	3" Bulls Eye Indicators.
HIT/ERROR	3" Bulls Eye Indicators.
CAPTIONS	White vinyl letters.
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels made from shatter resistant polycarbonate (Black, Dark Blue, Bright Blue, Violet, Maroon, Red, Dark Green, Green, custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL CONSOLE	Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Twisted pair, direct burial RJ45 Connectors.
POWER REQUIREMENTS	115 VAC, 60 Hz Minimum one 20A circuit is recommended.
INSTALLATION	May be installed on two posts. Mounting brackets are supplied with scoreboard.
WEIGHT	Net 210 lbs. / Shipping 260 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.