

ARCHITECTS SPECIFICATIONS MODEL 8418 LED FOOTBALL SCOREBOARD

OUTDOOR SCOREBOARD 8418 FOOTBALL	HOME CUEST TOLL TOLL DOWN TO GO BALL ON QTR
OVERALL DIMENSION	8' high x 18' wide x 4.75" deep.
INFORMATION DISPLAYED	Game Time, Home Score, Guest Score, Time Outs Left, Down, To Go, Ball On, Quarter
DIGITS	Bright Red, 7-Segment LEDs
TIMER	24" High Digits, Shall register 0:00 - 99:59
SCORING	21" High Digits, Shall register 0-99.
QUARTER	21" High Digits, Shall register 1-4.
DOWN	21" High Digits, Shall register 1-4.
TO GO	21" High Digits, Shall register 1-99.
BALL ON	21" High Digits, Shall register 1-99.
TIME OUTS LEFT	14" High Digits, Shall register 0-9.
CAPTIONS	White vinyl captions.
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal, finished in choice of colors (Black, Dark Blue, Bright Blue, Violet, Maroon, Red, Dark Green, Green, custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL CONSOLE	Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Two (2) twisted pair, direct burial.
POWER REQUIREMENTS	115 VAC. One 20A circuit is recommended.
INSTALLATION	May be installed on two posts. Mounting brackets are supplied with scoreboard.
WEIGHT	Net 563 lbs. / Shipping 700 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.