

## ARCHITECTS SPECIFICATIONS **MODEL 8782 LED SOCCER SCOREBOARD**

## **OUTDOOR SCOREBOARD HOME** Soccer 1st Half 2nd **Football** C. KICKS C. KICKS S.O.G. S.O.G. ALL AMERICAN TO GO BALL ON DOWN FOOTBALL CONVERSION KIT SOLD SEPARATERLY **OVERALL DIMENSION** 8' high x 18' wide x 4.75" deep. Game Time, Home Score, Guest Score, Shots on Goal, Corner Kicks, Half **INFORMATION DISPLAYED DIGITS** Bright Red, 7-Segment LEDs TIMER 24" High Digits, Shall register 0:00 - 99:59 **SCORING** 21" High Digits, Shall register 0-99. 21" High Digits, Shall register 0-99. SHOTS ON GOAL 21" High Digits, Shall register 0-99. **CORNER KICKS** HALF 4" Bullseye Indicators. **CAPTIONS** White vinyl captions. CONSTRUCTION 4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal, finished in choice of colors (Black, Navy, Blue, Bright Blue, Purple, Burgundy, Red, Forest Green, Green, custom colors available). **ELECTRONICS** 100% solid state, microprocessor controlled system. SERVICING Front access for ease of servicing. Plug in modules for ease of replacement. Extruded Aluminum, high impact low profile microprocessor control console, latest MICROPROCESSOR CONTROL state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. **CONSOLE** ALL AMERICAN Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available. **JUNCTION BOX** One junction box 5" x 3" with cover and plug. (Hardwire) Twisted pair, direct burial, RJ45 connectors. **DATA CABLE POWER REQUIREMENTS** 115 VAC. One 20A circuit is recommended. INSTALLATION May be installed on two posts. Mounting brackets are supplied with scoreboard. WEIGHT Net 563 lbs. / Shipping 700 lbs. **WARRANTY** Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label. UL Certified.